

EMC TEST REPORT

On Behalf of

Product Name : Pet LED light cutting and grinding machine

Trademark: N/A

Model Number: YR-802

Prepared For: Wenzhou Yingrong Daily Necessities Co., Ltd

Address: Building 3, 3rd Floor, No. 30-70 Xingqiang Road, Electromechanical
Entrepreneurship Park, Wanquan Town, Pingyang County, Wenzhou City,
Zhejiang Province

Prepared By: Shenzhen Huaxiang Testing Co., Ltd

Address: 1st Floor, Building A1, No. 2082 Jincheng Road, Shajing Street, Bao'an
District, Shenzhen City, Guangdong Province

Report No.: HUAX250916711KR

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 TEST STANDARDS	5
1.3 TEST SUMMARY	6
1.4 TEST METHODOLOGY	7
1.5 TEST FACILITY	7
1.6 TEST EQUIPMENT LIST AND DETAILS	8
2. SYSTEM TEST CONFIGURATION	10
2.1 JUSTIFICATION	10
2.2 EUT EXERCISE SOFTWARE	10
2.3 SPECIAL ACCESSORIES	10
2.4 EQUIPMENT MODIFICATIONS	10
2.5 CONFIGURATION OF TEST SYSTEM	10
2.6 TEST SETUP DIAGRAM	10
3. DISTURBANCE VOLTAGE AT THE MAINS TERMINALS	11
3.1 MEASUREMENT UNCERTAINTY	11
3.2 LIMIT OF DISTURBANCE VOLTAGE AT THE MAINS TERMINALS	11
3.3 EUT SETUP	11
3.4 INSTRUMENTS SETUP	12
3.5 TEST PROCEDURE	12
3.6 SUMMARY OF TEST RESULTS	12
3.7 DISTURBANCE VOLTAGE TEST DATA	12
3.8 TEST RESULT	12
4. DISCONTINUOUS DISTURBANCE (CLICK)	13
4.1 LIMIT OF DISCONTINUOUS DISTURBANCE	13
4.2 EUT SETUP	13
4.3 TEST PROCEDURE	13
4.4 SUMMARY OF TEST RESULTS	13
4.5 DISTURBANCE VOLTAGE TEST DATA	13
4.6 TEST RESULT	13
5. DISTURBANCE POWER	14
5.1 MEASUREMENT UNCERTAINTY	14
5.2 LIMIT OF DISTURBANCE POWER	14
5.3 EUT SETUP	14
5.4 INSTRUMENTS SETUP	15
5.5 TEST PROCEDURE	15
5.6 DISTURBANCE POWER TEST DATA	15
5.7 TEST PLOT(S) FOR DISTURBANCE POWER	15
5.8 TEST RESULT	15
6. RADIATED EMISSION MEASUREMENT	16
6.1 BLOCK DIAGRAM OF TEST	16
6.2 MEASURING STANDARD	16
6.3 RADIATED EMISSION LIMITS	17
6.4 EUT CONFIGURATION ON TEST	17
6.5 OPERATING CONDITION OF EUT	17
6.6 TEST PROCEDURE	17
6.7 MEASURING RESULTS	17
7. ELECTROSTATIC DISCHARGE IMMUNITY TEST (EN 61000-4-2)	20
7.1 BLOCK DIAGRAM OF TEST SETUP	20
7.2 TEST STANDARD	20
7.3 SEVERITY LEVELS AND PERFORMANCE CRITERION	20
7.4 OPERATING CONDITION OF EUT	20
7.5 TEST PROCEDURE	21
7.6 TEST RESULTS	21
8.0 RF FIELD STRENGTH SUSCEPTIBILITY TEST	23
8.1 BLOCK DIAGRAM OF TEST	23

8.2 TEST STANDARD	23
8.3 SEVERITY LEVELS AND PERFORMANCE CRITERION	24
8.4 EUT CONFIGURATION ON TEST	24
8.5 OPERATING CONDITION OF EUT	24
8.6 TEST PROCEDURE	24
8.7 TEST RESULTS	24
9. ELECTRICAL FAST TRANSIENT/BURST IMMUNITY TEST (EN 61000-4-4)	25
9.1 BLOCK DIAGRAM OF TEST SETUP	25
9.2 TEST STANDARD	25
9.3 SEVERITY LEVELS AND PERFORMANCE CRITERION	25
9.4 OPERATING CONDITION OF EUT	25
9.5 TEST PROCEDURE	26
9.6 TEST RESULT	26
10. SURGE IMMUNITY TEST (EN 61000-4-5)	27
10.1 BLOCK DIAGRAM OF TEST SETUP	27
10.2 TEST STANDARD	27
10.3 SEVERITY LEVELS AND PERFORMANCE CRITERION	27
10.4 OPERATING CONDITION OF EUT	27
10.5 TEST PROCEDURE	28
10.6 TEST RESULT	28
11. CONDUCTED SUSCEPTIBILITY TEST (EN 61000-4-6)	29
11.1 BLOCK DIAGRAM OF TEST SETUP	29
11.2 TEST STANDARD	29
11.3 SEVERITY LEVELS AND PERFORMANCE CRITERION	29
11.4 OPERATING CONDITION OF EUT	29
11.5 TEST PROCEDURE	30
11.6 TEST RESULTS	30
12. VOLTAGE DIPS, SHORT INTERRUPTIONS IMMUNITY TESTS (EN61000-4-11)	31
12.1 BLOCK DIAGRAM OF TEST SETUP	31
12.2 TEST STANDARD	31
12.3 SEVERITY LEVELS AND PERFORMANCE CRITERION	31
12.4 EUT CONFIGURATION	31
12.5 OPERATING CONDITION OF EUT	31
12.6 TEST PROCEDURE	32
12.7 TEST RESULT	32
13. TEST RESULTS	33
13.1 EN 61000-4-2 ELECTROSTATIC DISCHARGE IMMUNITY TEST CONFIGURATION	33
13.2 EN 61000-4-3 ELECTROSTATIC DISCHARGE IMMUNITY TEST CONFIGURATION	33
13.3 EN 61000-4-4 ELECTRICAL FAST TRANSIENT/BURST IMMUNITY TEST CONFIGURATION	33
13.4 EN 61000-4-5 SURGE IMMUNITY TEST CONFIGURATION	33
13.5 EN 61000-4-6 CONDUCTED SUSCEPTIBILITY TEST CONFIGURATION	33
13.6 EN 61000-4-11 VOLTAGE DIPS, SHORT INTERRUPTIONS IMMUNITY TESTS CONFIGURATION	33
APPENDIX A - PRODUCT LABELING	34
CE MARK LABEL SPECIFICATION	34
APPENDIX B- EUT PHOTOGRAPHS	35

TEST REPORT DECLARATION

Applicant	:	Wenzhou Yingrong Daily Necessities Co., Ltd
Address :	:	Building 3, 3rd Floor, No. 30-70 Xingqiang Road, Electromechanical Entrepreneurship Park, Wanquan Town, Pingyang County, Wenzhou City, Zhejiang Province
Manufacturer:	:	Wenzhou Yingrong Daily Necessities Co., Ltd
Address :	:	Building 3, 3rd Floor, No. 30-70 Xingqiang Road, Electromechanical Entrepreneurship Park, Wanquan Town, Pingyang County, Wenzhou City, Zhejiang Province
EUT Description :	:	Pet LED light cutting and grinding machine
Model Number	:	YR-802
Test Date		Sep. 16, 2025 – Sep. 22, 2025
Date of Report		Sep. 22, 2025

Test Standards:

EN IEC 55014-1: 2021
EN IEC 55014-2: 2021

The EUT described above is tested by Huaxiang Testing Co., Ltd. EMC Laboratory to determine the maximum emissions from the EUT and ensure the EUT to be compliance with the immunity requirements of the EUT. Shenzhen Huaxiang Testing Co., Ltd. is assumed full responsibility for the accuracy of the test results. Also, this report shows that the EUT technically complies with the 2014/30/EU directive and its amendment requirements.

The test report is valid for above tested sample only and shall not be reproduced in part without written approval of the laboratory.

Prepared by(Test Engineer):

Kevin Su

Kevin Su

Amy Jiang

Amy Jiang

Approved(Manager)

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant:	Wenzhou Yingrong Daily Necessities Co., Ltd
Address of applicant:	Building 3, 3rd Floor, No. 30-70 Xingqiang Road, Electromechanical Entrepreneurship Park, Wanquan Town, Pingyang County, Wenzhou City, Zhejiang Province
Manufacturer:	Wenzhou Yingrong Daily Necessities Co., Ltd
Address of manufacturer:	Building 3, 3rd Floor, No. 30-70 Xingqiang Road, Electromechanical Entrepreneurship Park, Wanquan Town, Pingyang County, Wenzhou City, Zhejiang Province

General Description of E.U.T

EUT Description:	Pet LED light cutting and grinding machine
Trade Mark:	N/A
EUT Model No.:	YR-802
Rating:	Rated Voltage:DC 5V
Test Voltage:	DC 5V

Remark:

- The test data gathered are from the production sample provided by the manufacturer.
- The length of power line is 1.8m

1.2 Test Standards

The following Declaration of Conformity report of EUT is prepared in accordance with

EN IEC 55014-1: 2021

EN IEC 55014-2: 2021

The objective of the manufacturer is to demonstrate compliance with the described standards above.

1.3 Test Summary

For the EUT described above. This apparatus is subdivided into category III according to the section 4.2 of EN IEC 55014-2: 2021. So according to section 7.2.2 of this standard, the immunity test item applicable to this EUT is listed in table 2.

Table 1: Tests Carried Out Under EN IEC 55014-1: 2021 (as amended)

Standard	Test Items	Test Result
EN IEC 55014-1: 2021	Conducted Emission, 150kHz to 30MHz	PASS
EN IEC 55014-1: 2021	Disturbance Power (30MHz To 300MHz)	N/A
EN IEC 55014-1: 2021	Click	N/A

- √ Indicates that the test is applicable
 × Indicates that the test is not applicable

Table 2: Tests Carried Out Under EN IEC 55014-2: 2021

Standard	Test Items	Test Result
EN 61000-4-2: 2009	Electrostatic discharge Immunity	PASS
EN 61000-4-3: 2006 +A1:2008+A2:2010	Radiated Susceptibility (80MHz to 1GHz)	N/A
EN 61000-4-4: 2004+A1:2010	Electrical Fast Transient/Burst Immunity	N/A
EN 61000-4-5: 2006	Surge Immunity	N/A
EN 61000-4-6: 2009	Conducted Susceptibility (150kHz to 230MHz)	N/A
EN 61000-4-11: 2004	Voltage Dips, Short Interruptions Immunity	N/A

- √ Indicates that the test is applicable
 × Indicates that the test is not applicable

1.4 Test Methodology

All measurements contained in this report were conducted with CISPR 16-1, radio disturbance and immunity measuring apparatus, and CISPR16-2, Method of measurement of disturbances and immunity.

All measurement required was performed at laboratory of Shenzhen Huaxiang Testing Co., Ltd. .

1.5 Test Facility

The test facility is recognized, certified, or accredited by the following comanizations:

EMC Lab. : Accredited by FCC (Federal Communications Commission)
The Laboratory has been assessed according to the requirements ISO/IEC 17025.

Name of Firm : Shenzhen Huaxiang Testing Co., Ltd. .

The facility also complies with the radiated and AC line conducted test site criteria set forth in CISPR 16-1, CISPR16-2.

1.6 Test Equipment List and Details

Table 1: Test Equipment for Emission Test and Harmonic Current / Flicker Test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal	Calibration Period
Ultra-Broadband Antenna	ROHDE & SCHWARZ	HL562	100015	Nov. 20, 2024	1 year
EMI Test Receiver	ROHDE & SCHWARZ	ESI 26	100009	Nov. 20, 2024	1 year
RF Test Panel	ROHDE & SCHWARZ	TS / RSP	335015/ 0017	N/A	N/A
Turntable	ETS	2088	2149	N/A	N/A
Antenna Mast	ETS	2075	2346	N/A	N/A
EMI Test Receiver	ROHDE & SCHWARZ	ESCS30	100038	Nov. 20, 2024	1 year
Artificial Mains	ROHDE & SCHWARZ	ESH2-Z5	100028	Nov. 20, 2024	1 year
Pulse Limiter	ROHDE & SCHWARZ	ESHSZ2	100044	Nov. 20, 2024	1 year
Absorbing Clamp	ROHDE & SCHWARZ	MDS-21	100011	Nov. 20, 2024	1 year
EMI In Motion	HD	KMS 560	560/385 BJ:01	N/A	N/A
Controller	HD	HD 050	050/477 BJ:01	N/A	N/A
Purified Power Source	CALIFORNIA INSTRUMENTS	HFS500	54513	Nov. 20, 2024	1 year
Harmonic And Flicker Analyzer	EM TEST	DPA503S1	0500-10	Nov. 20, 2024	1 year

Table 2: Test Equipment for Immunity Test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal	Calibration Period
ESD Simulator	EM TEST	DITOC0103Z	0301-04	Nov. 20, 2024	1 year
Signal Generator	IFR	2032	203002/100	Nov. 20, 2024	1 year
Amplifier	AR	140W1000	301584	Nov. 20, 2024	1 year
Dual Directional Coupler	AR	DC6080	301508	Nov. 20, 2024	1 year
Power Head	AR	PH2000	301193	Nov. 20, 2024	1 year
Power Meter	AR	PM2002	302799	Nov. 20, 2024	1 year
Ultra Compact Simulator	EM TEST	UCS500M6	0500-19	Nov. 20, 2024	1 year
Signal Generator	IFR	2023A	202304/060	Nov. 20, 2024	1 year
Amplifier	AR	75A250	302205	Nov. 20, 2024	1 year
Dual Directional Coupler	AR	DC2600	302389	Nov. 20, 2024	1 year
6DB Attenuator	EMTEST	ATT6/75	0010230A	Nov. 20, 2024	1 year
CDN	EMTEST	CDN M3	0802-03	Nov. 20, 2024	1 year
Ultra Compact Simulator	EM TEST	UCS500M6	0500-19	Nov. 20, 2024	1 year
Motor Driven Voltage Transformer	EM TEST	MV2616	0301-11	Nov. 20, 2024	1 year
Current Transformer	EM TEST	MC2630	D5101	Nov. 20, 2024	1 year
Magnetic Coil	EM TEST	MS100	0500-19	Nov. 20, 2024	1 year

2. SYSTEM TEST CONFIGURATION

2.1 Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).

2.2 EUT Exercise Software

The EUT exercising program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The software offered by manufacture, can let the EUT being normal operation.


2.3 Special Accessories

As shown in section 2.5, interface cable used for compliance testing is shielded as normally supplied by Wenzhou Yingrong Daily Necessities Co., Ltd. and its respective support equipment manufacturers.


2.4 Equipment Modifications

The EUT tested was not modified by HSO.

2.5 Configuration of Test System



2.6 Test Setup Diagram



3.1 Measurement Uncertainty

The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is ± 2.4 dB.

Frequency Range (MHz)	Limits (dBuV)	
	Quasi-Peak	Average
0.150~0.500	66~56	56~46
0.500~5.000	56	46
5.000~30.00	60	50

Note: (1) The tighter limit shall apply at the edge between two frequency bands.


3.3 EUT Setup

The EUT was placed center and the back edge of the test table.

The AV cables were draped along the test table and bundled to 30-40cm in the middle.

The spacing between the peripherals was 10 cm.

Maximum emission emitted from EUT was determined by manipulating the EUT, support equipment, interconnecting cables and varying the mode of operation and the levels in the final result of the test were recorded with the EUT running in the operating mode that maximum emission was emitted.



3.4 Instruments Setup

The test receiver was set with the following configurations:

Test Receiver Setting:

Frequency Range.....150 KHz to 30 MHz
Detector.....Peak & Quasi-Peak & Average
Sweep Speed.....Auto
IF Band Width.....9 KHz

3.5 Test Procedure

During the conducted emission test, the EUT power cord was connected to the auxiliary outlet of the first Artificial Mains.

Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance using all installation combination.

All data was recorded in the peak detection mode. Quasi-peak and Average readings were only performed when an emission was found to be marginal (within -10 dB μ V of specification limits). Quasi-peak readings are distinguished with a "QP". Average readings are distinguished with a "AV".

3.6 Summary of Test Results

According to the data in section 3.6, the EUT complied with the EN 55014-1 Conducted margin.

5 Disturbance Voltage Test Data

Temperature (°C)	22~25
Humidity (%RH)	50~55
Barometric Pressure (mbar)	950~1000
EUT	<u>Pet LED light cutting and grinding machine</u>
M/N	YR-802
Operating Mode	Normal

Test data see following pages

3.8 Test Result

N/A

4.1 Limit of Discontinuous Disturbance

4.2 EUT Setup

The spacing between the peripherals was 10 cm.

[illegible]

4.3 Test Procedure

During the Click test, the EUT power cord was connected to the auxiliary outlet of the first Artificial Mains Test Procedure details see clause 7.4.2 of standard EN 55014-1: 2006+A1:2009

4.4 Summary of Test Results

According to the data in section 4.3, the EUT complied with the requirement of Click test of EN 55014-1.

4.5 Disturbance Voltage Test Data

Temperature (°C)	22~25
Humidity (%RH)	50~54
Barometric Pressure (mbar)	950~1000
EUT	N/A
M/N	N/A
Operating Mode	N/A

4.6 Test Result

N/A

5. DISTURBANCE POWER

5.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and power clamp.

The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is ± 2.4 dB.

5.2 Limit of Disturbance Power

Frequency Range (MHz)	Limit (dBpW)	
	Quasi-Peak	Average
30~300	45~55	35~45

Note: (1) The limit line is a linear line.


5.3 EUT Setup

The setup of EUT is according with CISPR 16-1, CISPR16-2 measurement procedure. See following test setup figure. The specification used was the EN 55014-1 limits.

The EUT was placed at the edge of the test table so as to make the end of the lead close to the EUT as short as possible between the power clamp and the EUT.

The spacing between the peripherals was 10 cm.

Maximum emission emitted from EUT was determined by manipulating the EUT, support equipment, interconnecting cables and varying the mode of operation and the levels in the final result of the test were recorded with the EUT running in the operating mode that maximum emission was emitted



5.4 Instruments Setup

The test receiver was set with the following configurations:

Test Receiver Setting:

Frequency Range.....30MHz to 300 MHz
Detector.....Peak & Quasi-Peak & Average
Sweep Speed.....Auto
IF Band Width.....9 KHz

5.5 Test Procedure

The associated equipment under test is placed on a non-metallic table of 0.8 m of height above the floor and at least 0.4 m from other objects and from any person. The lead to be measured shall be stretched in a straight horizontal line for a length sufficient to accommodate the absorbing clamp and to permit the necessary adjustment of its position for tuning. The absorbing clamp is placed around the lead to be measured, with its current transformer towards the equipment under test, so as to measure a quantity proportional to the disturbance power on the lead.

Any other lead less than that to be measured shall either be disconnected, if mechanically and functionally possible, or fitted with ferrite rings to attenuate RF currents which may affect the measurement results. Such a lead shall be stretched away from the connected unit in a direction perpendicular to the direction of the lead to be measured.

All connectors not used shall be left un-terminated. All connectors having a connected lead shall be terminated in a manner representative of use. If the leads are screened and normally terminated in a screened unit, then the termination shall be screened.

5.6 Disturbance Power Test Data

Temperature (°C)	22~23
Humidity (%RH)	50~54
Barometric Pressure (mbar)	950~1000
EUT	Pet LED light cutting and grinding machine
M/N	YR-802
Operating Mode	Normal

5.7 Test Plot(s) for Disturbance Power

Plot(s) of Disturbance Power Test Data is presented hereinafter as reference.


5.8 Test Result

N/A

6. RADIATED EMISSION MEASUREMENT

6.1 Block Diagram of Test

Block diagram of test setup (In chamber)



6.2 Measuring Standard

EN IEC 55014-1: 2021

6.3 Radiated Emission Limits

All emanations from a class B device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified below:

FREQUENCY (MHz)	DISTANCE (Meters)	FIELD STRENGTHS LIMIT (dB μ V/m)
30 ~ 230	3	40
230 ~ 1000	3	47

Note: (1) The smaller limit shall apply at the combination point between two frequency bands.

(2) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the EUT.

6.4 EUT Configuration on Test

The EN61000-6-3 regulations test method must be used to find the maximum emission during radiated emission measurement.

6.5 Operating Condition of EUT

Turn on the power.

After that, let the EUT work in test mode (Normal) and measure it.

6.6 Test Procedure

The EUT is placed on a turn table which is 0.8 meter high above the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Bilog antenna (calibrated by Dipole Antenna) is used as a receiving antenna. Both horizontal and vertical polarization of the antenna are set on test.

The bandwidth of the Receiver (ESCS30) is set at ES1kHz.


The frequency range from 30MHz to 1000MHz is investigated.

6.7 Measuring Results

PASS.


Please reference to the following pages

Standard:	EN IEC 55014-1: 2021	Polarization:	Horizontal
Test item:	Radiation Test	Date:	2025-09-17
EUT:	Pet LED light cutting and grinding machine	Test By:	Mark
Model:	YR-802	Distance:	3m
Note:			



Suspected Data List											
NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Det	Pol	Verdict
1	32.3040	36.00	24.08	-11.92	40.00	15.92	100	85	PK	Hori	PASS
2	56.5571	34.98	19.07	-15.91	40.00	20.93	100	185	PK	Hori	PASS
3	156.3583	32.94	18.00	-14.94	40.00	22.00	100	306	PK	Hori	PASS
4	173.9417	44.09	27.65	-16.44	40.00	12.35	100	306	PK	Hori	PASS
5	316.9134	39.64	24.18	-15.46	47.00	22.82	100	185	PK	Hori	PASS
6	579.8162	35.13	24.95	-10.18	47.00	22.05	100	185	PK	Hori	PASS

Standard:	EN IEC 55014-1: 2021	Polarization:	Vertical
Test item:	Radiation Test	Date:	2025-09-17
EUT:	Pet LED light cutting and grinding machine	Test By:	Mark
Model:	YR-802	Distance:	3m
Note:			




Suspected Data List

NO.	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Det	Pol	Verdict
1	104.9419	31.80	13.19	-18.61	40.00	26.81	100	214	PK	Vert	PASS
2	145.6870	26.41	11.16	-15.25	40.00	28.84	100	10	PK	Vert	PASS
3	287.4459	34.56	18.35	-16.21	47.00	28.65	100	259	PK	Vert	PASS
4	530.5826	45.81	34.69	-11.12	47.00	12.31	100	183	PK	Vert	PASS
5	792.1515	38.32	31.47	-6.85	47.00	15.53	100	307	PK	Vert	PASS
6	829.5012	43.53	36.97	-6.56	47.00	10.03	100	331	PK	Vert	PASS

7. ELECTROSTATIC DISCHARGE IMMUNITY TEST (EN 61000-4-2)


7.1 Block Diagram of Test Setup

9.1.1 Block diagram of connection between the EUT and Load



(EUT: Pet LED light cutting and grinding machine)

7.1.2 Block diagram of ESD test setup



7.2 Test Standard

EN IEC 55014-2: 2021 , (EN61000-4-2: 2009 Severity Level: 3 / Air Discharge: $\pm 8\text{KV}$ Level: 2 / Contact Discharge: $\pm 4\text{KV}$)

7.3 Severity Levels and Performance Criterion

7.3.1 Severity level

Level	Test Voltage Contact Discharge (KV)	Test Voltage Air Discharge (KV)
1	± 2	± 2
2	± 4	± 4
3	± 6	± 8
4	± 8	± 15
X	Special	Special

7.3.2 Performance criterion: B

7.4 Operating Condition of EUT

7.4.1 Setup the EUT as shown on Section 8.1.

7.4.2 Turn on the power of all equipments.

7.4.3 Let the EUT work in measuring mode (Normal) and measure it.

7.5 Test Procedure

7.5.1 Air Discharge:

This test is done on a non-conductive surface. The round discharge tip of the discharge electrode shall be approached as fast as possible to touch the EUT. After each discharge, the discharge electrode shall be removed from the EUT. The generator is then re-triggered for a new single discharge and repeated 10 times for each pre-selected test point. This procedure shall be repeated until all the air discharge completed.

7.5.2 Contact Discharge:

All the procedure shall be same as Section 8.5.1. Except that the tip of the discharge electrode shall touch the EUT before the discharge switch is operated.

7.5.3 Indirect discharge for horizontal coupling plane

At least 10 single discharges (in the most sensitive polarity) shall be applied at the front edge of each HCP opposite the center point of each unit (if applicable) of the EUT and 0.1m from the front of the EUT. The long axis of the discharge electrode shall be in the plane of the HCP and perpendicular to its front edge during the discharge.

7.5.4 Indirect discharge for vertical coupling plane

At least 10 single discharge (in the most sensitive polarity) shall be applied to the center of one vertical edge of the coupling plane. The coupling plane, of dimensions 0.5m X 0.5m, is placed parallel to, and positioned at a distance of 0.1m from the EUT. Discharges shall be applied to the coupling plane, with this plane in sufficient different positions that the four faces of the EUT are completely illuminated.

7.6 Test Results

PASS

Please refer to the following page.

Temperature (°C)	22~23
Humidity (%RH)	50~54
Barometric Pressure (mbar)	950~1000
EUT	Pet LED light cutting and grinding machine
M/N	YR-802
Operating Mode	Normal

Table 1: Electrostatic Discharge Immunity (Air Discharge)

EN 61000-4-2 Test Points	Test Levels									
	-2 kV	+2 kV	-4 kV	+4 kV	-6 kV	+6 kV	-8 kV	+8 kV	-15 kV	+15 kV
Gap	A	A	A	A	A	A	A	A	/	/
Switch	A	A	A	A	A	A	A	A	/	/

Table 2: Electrostatic Discharge Immunity (Direct Contact)

EN 61000-4-2 Test Points	Test Levels									
	-2 kV	+2 kV	-4 kV	+4 kV	-6 kV	+6 kV	-8 kV	+8 kV	-15 kV	+15 kV
Screw	A	A	A	A	/	/	/	/	/	/

Table 3: Electrostatic Discharge Immunity (Indirect Contact HCP)

EN 61000-4-2 Test Points	Test Levels									
	-2 kV	+2 kV	-4 kV	+4 kV	-6 kV	+6 kV	-8 kV	+8 kV	-15 kV	+15 kV
Front Side	A	A	A	A	/	/	/	/	/	/
Top Side	A	A	A	A	/	/	/	/	/	/
Back Side	A	A	A	A	/	/	/	/	/	/
Left Side	A	A	A	A	/	/	/	/	/	/
Right Side	A	A	A	A	/	/	/	/	/	/


Table 4: Electrostatic Discharge Immunity (Indirect Contact VCP)

EN 61000-4-2 Test Points	Test Levels									
	-2 kV	+2 kV	-4 kV	+4 kV	-6 kV	+6 kV	-8 kV	+8 kV	-15 kV	+15 kV
Front Side	A	A	A	A	/	/	/	/	/	/
Top Side	A	A	A	A	/	/	/	/	/	/
Back Side	A	A	A	A	/	/	/	/	/	/
Left Side	A	A	A	A	/	/	/	/	/	/
Right Side	A	A	A	A	/	/	/	/	/	/


8. RF FIELD STRENGTH SUSCEPTIBILITY TEST

8.1 Block Diagram of Test

8.1.1 Block diagram of connection between the EUT and Load



8.1.2 Block diagram of RS test setup



8.2 Test Standard

EN IEC 55014-2: 2021

(EN61000-4-3:2006 +A1:2008+A2:2010 (Severity Level: 2, 3.7V / m))

8.3 Severity Levels and Performance Criterion

8.3.1 Severity Levels

Level	Field Strength V/m
1.	1
2.	3
3.	10
X	Special

8.3.2 Performance Criterion : A

8.4 EUT Configuration on Test

The configuration of the EUT is same as Section 3.3.

8.5 Operating Condition of EUT

Same as radiated emission measurement which is listed in Section 3.4, except the test setup replaced as Section 8.1.

8.6 Test Procedure

The EUT are placed on a table which is 0.8 meter high above the ground. The EUT is set 3 meters away from the transmitting antenna which is mounted on an antenna tower. Both horizontal and vertical polarization of the antenna are set on test. Each of the four sides of the EUT must be faced this transmitting antenna and measured individually. In order to judge the EUT performance, a CCD camera is used to monitor its screen. All the scanning conditions are as following:

Condition of Test	Remark
1. Fielded Strength	3.7V/m (Severity Level 2)
2. Radiated Signal	Modulated
3. Scanning Frequency	80-1000MHz
4. Sweep time of radiated	0.0015 Decade/s
5. Dwell Time	1 Sec.


8.7 Test Results

N/A


9. ELECTRICAL FAST TRANSIENT/BURST IMMUNITY TEST (EN 61000-4-4)

9.1 Block Diagram of Test Setup

9.1.1. Block Diagram of the EUT



9.1.2. Block Diagram of the AC Mains



9.2 Test Standard

EN IEC 55014-2: 2021 , (EN61000-4-4: 2004+A1: 2010, Severity Level, Level 2: 1KV)

9.3 Severity Levels and Performance Criterion

9.3.1 Severity level

Open Circuit Output Test Voltage $\pm 10\%$		
Level	On Pet LED light cutting and grinding machineLines	On I/O (Input/Output) Signal data and control lines
1	0.5 KV	0.25 KV
2	1 KV	0.5 KV
3	2 KV	1 KV
4	4 KV	2 KV
X	Special	Special

9.3.2 Performance criterion: B

9.4 Operating Condition of EUT

9.4.1 Setup the EUT as shown in Section 9.1.

9.4.2 Turn on the power of all equipments.

9.4.3 Let the EUT work in test mode (Normal) and measure it.

9.5 Test Procedure

The EUT is put on the table which is 0.8 meter high above the ground. This reference ground plane shall project beyond the EUT by at least 0.1m on all sides and the minimum distance between EUT and all other conductive structure, except the ground plane beneath the EUT, shall be more than 0.5m.

9.5.1 For input and output AC power ports:
It's unnecessary to test

9.5.2 For signal lines and control lines ports:
It's unnecessary to test.

9.5.3 For DC Input line ports:

The EUT is connected to the DC power mains by using a coupling device which couples the EFT interference signal to DC power lines. Both polarities of the test voltage should be applied during compliance test and the duration of the test is 2 mins.


9.6 Test Result

N/A


10. SURGE IMMUNITY TEST (EN 61000-4-5)

10.1 Block Diagram of Test Setup

10.1.1. Block Diagram of the EUT



10.1.2. Block Diagram of the AC Mains



10.2 Test Standard

EN IEC 55014-2: 2021 , (EN61000-4-5: 2006 Severity Level: Line to Line, Level 2: 1KV, Line to Earth , Level 3: 2KV)

10.3 Severity Levels and Performance Criterion

10.3.1. Severity level

Severity Level	Open-Circuit Test Voltage KV
1	0.5
2	1.0
3	2.0
4	4.0
*	Special

10.3.2 Performance criterion: B

10.4 Operating Condition of EUT

10.4.1 Setup the EUT as shown in Section 10 .1.

10.4.2. Turn on the power of all equipments.

10.4.3. Let the EUT work in test mode (Normal) and measure it.

10.5 Test Procedure

- 1)Set up the EUT and test generator as shown on Section 10 .1.2.
- 2)For DC port coupling mode, provide a 1 KV 1.2/50us voltage surge (at open-circuit condition) and 8/20us current surge to EUT selected points.
- 3)At least 5 positive and 5 negative (polarity) tests with a maximum 1/min repetition rate are conducted during test.
- 4)Record the EUT operating situation during compliance test and decide the EUT immunity criterion for above each test.

10.6 Test Result

N/A

11. CONDUCTED SUSCEPTIBILITY TEST (EN 61000-4-6)


11.1 Block Diagram of Test Setup

11.1.1. Block Diagram of the EUT



(EUT: Pet LED light cutting and grinding machine)

11.1.2. Block Diagram of the AC Mains



(EUT: Pet LED light cutting and grinding machine)

11.2 Test Standard

EN IEC 55014-2: 2021 (EN61000-4-6: 2009, Severity Level 2: 3.7V(rms)).
(0.15MHz ~ 230MHz)

11.3 Severity Levels and Performance Criterion

11.3.1. Severity level

Level	Field Strength V(r.m.s)
1	1
2	3
3	10
X	Special

11.3.2 Performance criterion: A

11.4 Operating Condition of EUT

11.4.1 Setup the EUT as shown in Section 11 .1.

11.4.2 Turn on the power of all equipments.

11.4.3 Let the EUT work in test mode (Normal) and measure it.

11.5 Test Procedure

11.5.1 For AC Mains

It's unnecessary to test.

11.5.2 For signal lines and control lines ports:

It's unnecessary to test.

11.5.3 For DC Input line ports:

- 1) Set up the EUT, CDN and test generators as shown on Section 11 .1.
- 2) Let the EUT work in test mode and measure it.
- 3) The EUT are placed on an insulating support 0.1m high above a ground reference plane. CDN (coupling and decoupling network) is placed on the ground plane about 0.3m from EUT. Cables between CDN and EUT are as short as possible, and their height above the ground reference plane shall be between 30 and 50 mm (where possible).
- 4) The disturbance signal described below is injected to EUT through CDN.
- 5) The EUT operates within its operational mode(s) under intended climatic conditions after power on.
- 6) The frequency range is swept from 150KHz to 230MHz using 3.7V signal level, and with the disturbance signal 80% amplitude modulated with a 1KHz sine wave.
- 7) The rate of sweep shall not exceed 1.5×10^{-3} decades/s. Where the frequency is swept incrementally, the step size shall not exceed 1% of the start and thereafter 1% of the preceding frequency value.

Recording the EUT operating situation during compliance testing and decide the EUT immunity criterion.

11.6 Test Results

N/A

12. VOLTAGE DIPS, SHORT INTERRUPTIONS IMMUNITY TESTS (EN61000-4-11)


12.1 Block Diagram of Test Setup

12.1.1. Block Diagram of the EUT



(EUT: Pet LED light cutting and grinding machine)

12.1.2. Block Diagram of the AC Mains



(EUT: Pet LED light cutting and grinding machine)

12.2 Test Standard

EN IEC 55014-2: 2021 (EN61000-4-11: 2004)

12.3 Severity Levels and Performance Criterion

Test Level %UT	Voltage dip and short interruptions %UT	Duration (in period)
0	100	0.5 1 5
40	60	10 25 50
70	30	*

Performance criterion: B&C

12.4 EUT Configuration

The configuration of EUT is listed in Section 12 .4.

12.5 Operating Condition of EUT

12.5.1 Turn on the power of all equipments.

12.5.2 Let the EUT work in test mode (Normal) and measure it.

12.6 Test Procedure

- 1)Set up the EUT and test generator as shown on Section 12 .1.2.
- 2)The interruption is introduced at selected phase angles with specified duration.
- 3)Record any degradation of performance.

12.7 Test Result

N/A



13. TEST RESULTS

The following tests were performed on the Wenzhou Yingrong Daily Necessities Co., Ltd.'s product; model: YR-802; the actual test results are contained within the Test Data section of this report.

13.1 EN 61000-4-2 Electrostatic Discharge Immunity Test Configuration

The EUT was subjected to the electrostatic discharge tests required by EN 55014-2 and all lower levels specified in EN 61000-4-2.

The EUT continued to perform as intended during and after the application of the ESD.

13.2 EN 61000-4-3 Electrostatic Discharge Immunity Test Configuration

The EUT was subjected to the electrostatic discharge tests required by EN 55014-2 and all lower levels specified in EN 61000-4-3.

N/A

13.3 EN 61000-4-4 Electrical Fast Transient/Burst Immunity Test Configuration

The EUT was subjected to the electrical fast transient tests required by EN 55014-2 and all lower levels specified in EN 61000-4-4.

N/A

13.4 EN 61000-4-5 Surge Immunity Test Configuration

The EUT was subjected to the Surge Immunity tests required by EN 55014-2 and all lower levels specified in EN 61000-4-5.

N/A

13.5 EN 61000-4-6 Conducted Susceptibility Test Configuration

The EUT was subjected to the Conducted Susceptibility tests required by EN 55014-2 and all lower levels specified in EN 61000-4-6.

N/A

13.6 EN 61000-4-11 Voltage Dips, Short Interruptions Immunity Tests Configuration

The EUT was subjected to the Voltage Dips/Interruptions tests required by EN 55014-2 and all lower levels specified in EN 61000-4-11.

N/A

Appendix A - Product Labeling

CE Mark Label Specification

Specification: Text is Black or white in color and is left justified. Labels are printed in indelible ink on permanent adhesive backing and shall be affixed at a conspicuous location on the EUT or Silk-screened onto the EUT.



Appendix B- EUT PHOTOGRAPHS




Photo 1



Photo 2



Photo 3




Photo 4




Photo 5



Photo 6




Photo 7




Photo 8




Photo 9




Photo 10




Photo 11




Photo 12

*****END OF THE REPORT*****